

COTEK AC switch-set TR 40 for SP-Serie

Features:

- power consumption < 1.3W
- Universal AC input / full program
- cooling by convection
- switch current up 40 A
- easy to use, free Setup
- high transmission speed

optional for Model SP 700 - SP 4000



| Model | | TR 40 |
|----------------|--|--|
| Contact Rating | Max. Switching Voltage | 277 VAC |
| | Max Switching Current | 40 A |
| | Max Switching Power | 11080 VA |
| | Switching time | INV to grid |
| grid to INV | | 10 m Sek |
| Control | Voltage range | 100 V - 240 VAC |
| | AC current (type) | 21 mA / 100 VAC 16 mA / 240 VAC |
| | Frequency range | 47 HZ - 63 Hz |
| | Power consumption | < 1,4 W (at no load) |
| Protection | Wiring errors | LED Information |
| | Grid overload | Circuit Breaker |
| Environment | Working temp. | - 20 °C - + 40 °C |
| | Working humidity | 20 - 85 % RH non condensing |
| | Storage temp. Humidity | - 40 - + 80 °C / 20 - 85 % RH |
| | Vibration | 10 - 500 Hz, 2G 10 min/1 cycle, periode for 60 min each along X,Y,Z axes |
| Safety & EMC | Safety Standard | EN60947-1 approved (only for TR-40C) |
| | EMI Conduction & Radiation | EN55022 |
| | Power Harmonic & Voltage Fluctuation & Flicker | EN61000-3-2 , EN61000-3-3 |
| | EMS Immunity | EN55024, IEC6100-4-2,3,4,5,6,8,11 |
| | Dimension (LxWxH) mm | 194 x 220 x 71 |