

## TECHNICAL DATA AND ACCESSORIES RESCUECHARGER IN 2X12A - 2X20A - 2X35A



RescueCharger	2 x 12 A	2 x 20 A	2 x 35 A
Item No. with Plugin	705700	706300	705100
Mains voltage VAC	230 V/50-60	230 V/50-60	230 V/50-60
Operating temperature	-35 bis + 50 °C	-35 bis + 50 °C	-35 bis + 50 °C
Charging voltage* S1 VDC	14,4	14,4	14,4
Float voltage S2 VDC	13,5	13,5	13,5
Charging current - A	2 x 12	2 x 20	2 x 35
Recommended battery max. Ah	2 x 150	2 x 250	2 x 600
IP-rate	44	44	44
Weight kg	2	3	4
Height/Width/Depth mm	138 x 201 x 53	182 x 190 x 53	200 x 190 x 53

RescueCharger Accessories	
706483	2 m Charging cable 20 A
706484	4 m Charging cable 20 A
706485	6 m Charging cable 20 A
705099	2 m Charging cable 35 A
705147	4 m Charging cable 35 A
705159	6 m Charging cable 35 A
715160	8 m Charging cable 35 A
705162	5 m Remote Panel 2x20A,2x35A
705163	10m Remote Panel 2x20A,2x35A
705164	20m Remote Panel 2x20A,2x35A
705165	25m Remote Panel 2x20A,2x35A
705463	Connection Schuko Plugin